emepowersolutions.com
+44 1829 863497

PRODUCT DATASHEET

MODEL P20 – BWP – 1 Ph

20.0 kVA	16.0 kW	18.2 KVA	14.6 KW
ESP	ESP	PRP	PRP

50 HZ | PRIME & STANDBY POWER



Illustration; final configuration may vary.

GENERATOR SET – KEY PARAMETERS

GENSET MODEL	P20 – BWP – 1Ph
POWER PRP	18.2 kVA / 14.6 kW
POWER ESP	20.0 kVA / 16.0 kW
FREQUENCY / SPEED	50 Hz / 1500 RPM
OUTPUT VOLTAGE	230 V
WIRING METHOD	1 - Phase, 4 - Wire
POWER FACTOR	0.8 pf lagging
ENCLOSURE TYPE	Silent (Sound Attenuated) 72 dBA @ 7m



Acoustic Vents



Premium DSE Controller



Easy Maintenance

DIESEL ENGINE

ENGINE BRAND	Perkins
ENGINE MODEL	404A-22G
OIL – WATER SEPERATOR	Self - contained
Battery Charger	Standard

ALTERNATOR

BRAND	Stamford
MODEL	S1L2-J1
SPACE HEATER	Included
EXCITATION	Brushless Self Exciting (AVR)
INSULATION CLASS	H / H
PROTECTION CLASS	IP23



DEEP SEA DSE

MADE IN BRITAIN

AUXILIARY SYSTEMS

CONTROL MODULE	DEEPSEA DSE 7320 MKII
COOLING RADIATOR	50 °C (122 °F) ambient
CIRCUIT BREAKER	Included
COOLANT HEATER	Optional
STARTING BATTERY	Included
FUEL TANK	110 litres Single Skin
BATTERY	Included

STANDARD SUPPLY

Installation Accessories	Corrugated vibration isolators, smoke bends, industrial silencers, standard connection parts, standard tools kit.
Documentation	Electrical drawings, operation & maintenance manuals, generator test report, certificates of conformity.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

emepowersolutions.com
+44 1829 863497

PRODUCT DATASHEET

MODEL P20 – BWP – 1 Ph

20.0 kVA	16.0 kW	18.2 KVA	14.6 KW
ESP	ESP	PRP	PRP

50 HZ | PRIME & STANDBY POWER

ENGINE TECHNICAL PARAMETERS - CUMMINS 6LTAA9.5-G1 - DIESEL

Structural Form	Four Stroke
Number of Cylinders	4 (In Line)
Displacement	2.21 L
Bore / Stroke	84mm / 100mm
Compression Ratio	23:3:1
Aspiration	Naturally Aspirated
Governor	Mechanical
Cooling Method	Closed Water Cooling
Speed	1500 RPM

LUBRICATION SYSTEM	
Total Lube Capacity	7.0 Liters
COOLING SYSTEM	
Coolant Capacity	10.6 Liters

Perkins® STAMFORD | AvK ™

FUEL CONSUMPTION

50% Load	75% Load	100% Load	110% Load
2.90 liters/hour	4.00 liters/hour	5.30 liters/hour	6.10 liters/hour

ALTERNATOR TECHNICAL PARAMETERS – Mecc Alte ECP28-2S4C

Rated Power	18.2 kVA / 14.6 kW
Number of Poles	4
Winding Number	T0405S3
Bearing Type	Single Bearing
Protection Class	IP23
Insulation Class	H
Excitation Method	Brushless Self-Exciting
Voltage Regulation	Model DSR
Telephone Impact Factor (TIF)	< 50
Telephone Harmonic Factor (THF)	< 2%
Space Heater	Included as standard

CONTROL SYSTEM - DSE 7320 MKII

BRAND	**Deep Sea Electronics**
Model	DSE 7320 MKII
Configurable Inputs / Outputs	6 digital + 3 analogue senders / 6
Key Features	Auto-start, auto mains failure (AMF) control, LED indicators

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

MODEL P20 – BWP – 1 Ph	20.0 kVA	16.0 kW	18.2 KVA	14.6 KW
50 HZ | PRIME & STANDBY POWER	ESP	ESP	PRP	PRP





DIMENSIONS & WEIGHT

Canopied or Open Type			
Canopy 2240 / Open 2200 LENGTH (mm)	Canopy 1038 / Open 1000 WIDTH (mm)	Canopy 1620 / Open 1535 HIGHT (mm)	Canopy 773.2 / Open 697.0 WEIGHT (kg)

RATING CONDITIONS

Reference Ambient Temperature	50 °C
Reference Altitude	1000 m above sea level
Frequency Regulation	± 0.25 Hz steady state
Voltage Regulation (AVR)	± 1% no-load to full load
Standards Compliance	ISO 8528, BS EN 60034

DISCLAIMER

All ratings are at 40 °C ambient temperature and 1000 m altitude unless stated otherwise. Prime power ratings apply to variable load operation for an unlimited number of hours. Standby ratings apply to supplying emergency power for the duration of a utility power outage. Derating may be required for elevated ambient temperatures or altitudes. ABB circuit breaker and AISIKAI ATS are available as factory-fitted options - confirm at time of order. In line with our policy of continuous product development, we reserve the right to change specification without notice.

Dealer contact details:

EME POWER

sales@emeps.net

+44 1829 863497 | emepowersolutions.com