emepowersolutions.com
+44 1829 863497

PRODUCT DATASHEET

MODEL P200-BWP

220 kVA	176 kW	200 kVA	160 kW
ESP	ESP	PRP	PRP

50 HZ | PRIME & STANDBY POWER



Illustration; final configuration may vary.

GENERATOR SET - KEY PARAMETERS

GENSET MODEL	P200-BWP
POWER PRP	200 kVA / 160 kW
POWER ESP	220 kVA / 176 kW
FREQUENCY / SPEED	50 Hz / 1500 RPM
OUTPUT VOLTAGE	400 / 230 V
WIRING METHOD	3-phase, 4-wire
POWER FACTOR	0.8 pf lagging
ENCLOSURE / NOISE	Canopied; 76 dB(A) @ 7 m

DIESEL ENGINE

ENGINE BRAND	Perkins
ENGINE MODEL	1106A-70TAG4
ASPIRATION	Turbocharged
GOVERNOR	Electronic

ALTERNATOR

BRAND	Stamford
MODEL	UCI274H1
EXCITATION	Self Excited
INSULATION CLASS	H
VOLTAGE REGULATION	1%
SPACE HEATER	Optional

AUXILIARY SYSTEMS

CONTROL MODULE	Deep Sea DSE 7320 MKII
COOLING RADIATOR	Tropical, 50 C ambient
FULL-LOAD CURRENT	317.5 A at ESP
CIRCUIT BREAKER	Optional; sized to generator rating
COOLANT HEATER	Optional
STARTING BATTERY	Wet battery, maintenance-free
FUEL TANK	325 litres
BASE FRAME	Base tank + AVM + battery holder



Acoustic Vents



Premium DSE Controller



Easy Maintenance

STANDARD SUPPLY

INSTALLATION ACCESSORIES	AVMs, exhaust connection, silencer, standard connection parts and tool kit.

MODEL P200-BWP

220 kVA	176 kW	200 kVA	160 kW
ESP	ESP	PRP	PRP

50 HZ | PRIME & STANDBY POWER

ENGINE TECHNICAL PARAMETERS - PERKINS 1106A-70TAG4 - DIESEL

STRUCTURAL FORM	4 Stroke	**COMBUSTION SYSTEM**	Direct Injection
NUMBER OF CYLINDERS	6 (In Line)	**OIL CAPACITY**	18.0L
DISPLACEMENT	7.01L	**COOLANT CAPACITY**	21.0L
BORE / STROKE	105mm / 135mm	**MAX EXHAUST TEMP.**	550 ºC
COMPRESSION RATIO	16:1	**EU EMISSIONS**	None
ASPIRATION	Turbocharged		
GOVERNOR	Electronic		
COOLING METHOD	Liquid Cooled		
SPEED	1500 RPM		

FUEL CONSUMPTION

50% Load	75% Load	100% Load	110% Load
23.10 litres/hour	34.70 litres/hour	45.80 litres/hour	49.40 litres/hour

ALTERNATOR TECHNICAL PARAMETERS - STAMFORD UCI274H1

RATED POWER AT 400 V	ESP 220.0 kVA / PRP 200.0 kVA
NUMBER OF POLES / LEADS	4 / 12
WINDING NUMBER	311
BEARING TYPE	1 bearing
PROTECTION CLASS	IP23
INSULATION CLASS	H
EXCITATION METHOD	Self Excited
VOLTAGE REGULATION	AS440 AVR / 1%
HARMONIC CONTENT	<5.00%
SHORT-CIRCUIT CAPACITY	>300%
SPACE HEATER	Optional

CONTROL SYSTEM - DSE 7320 MKII

BRAND	Deep Sea Electronics
MODEL	DSE 7320 MKII
CONFIGURABLE INPUTS / OUTPUTS	6 digital + 3 analogue senders / 6 outputs
KEY FEATURES	Auto-start, AMF control, LED indicators and event logging

emepowersolutions.com
+44 1829 863497

PRODUCT DATASHEET

MODEL P200-BWP

220 kVA	176 kW	200 kVA	160 kW
ESP	ESP	PRP	PRP

50 HZ | PRIME & STANDBY POWER



Illustration; final configuration may vary.

DIMENSIONS & WEIGHT

LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	WEIGHT (kg)
3208	1164	1778	2413.85

Configuration: UK/EU Canopied / frame 2400E / tank 325 L

RATING CONDITIONS

RATING BASIS	NTP conditions; confirm project derating requirements
FREQUENCY / SPEED	50 Hz / 1500 RPM
VOLTAGE / CONNECTION	400/230 V / series star
POWER FACTOR	0.8 lagging
COOLING PACKAGE	Tropical radiator rated for 50 C ambient
STANDARDS	ISO 8528; IEC 60034

DISCLAIMER

Ratings and component data are transcribed from the corresponding Welland Power configuration for 400 V, three-phase, 50 Hz operation and checked against the listed Perkins engine and Stamford alternator models. Dimensions, weight, tank and noise data apply only to the configuration stated above. Images are illustrative and are intentionally common across this range. Final build specification, GA drawing, breaker selection and site derating must be confirmed at order. Manufacturer specifications may change without notice.

Dealer contact details:

EME POWER

sales@emeps.net

+44 1829 863497 | emepowersolutions.com