

Illustration; final configuration may vary.

Perkins EnergyMax
P250-S | P275-S | P340-S

Perkins Powered Diesel Engine Coupled to Stamford AVK Alternator, Fully Designed in The United Kingdom Controlled by a DSE Auto Start Digital Controller.

Model	Perkins	Stamford	Deepsea	Prime	Standby	Phase
P250-S	1206A-E70TTAG2	UCDI274J	7320 MKII	225.0 kVA	250.0 kVA	3
P275-S	1206A-E70TTAG3	UCDI274K	7320 MKII	250.0 kVA	275.0 kVA	3
P340-S	1506A-E88TAG5	S4L1D-D	7320 MKII	310.0 kVA	340.0 kVA	3

EnergyMax Series Canopies default features

- Compatible with 2000/14/EC directives, certified noise emission level
- 2 or 4 points transport possibility according to canopy size.
- Hidden residential low noise exhaust built in the canopy.
- Emergency stop button located on the canopy
- Acoustic vents for Improved air suction channel to ensure homogenous cooling in the canopy.
- Radiator air outlet and exhaust with designed towards above
- Galvanised & Powder Coated against corrosion and rust.
- Improved performance in terms of sound insulation.



EnergyMax Base Frame & Fuel Tank

Base is manufactured from galvanised steel that has features and durability. Thanks to its rigid structural design and anti-vibration mounts, it reduces vibration level to minimum. Base frame contain lifting points to make transportation and positioning easy. With integrated modular fuel tank

DeepSea Electronics DSE7320 Controller

The DSE7310 is an Auto Start Control Module and the DSE7320 is an Auto Mains (Utility) Failure Control Module suitable for a wide variety of single, diesel or gas, gen-set applications.



Monitoring an extensive number of engine parameters, the modules will display warnings, shutdown and engine status information on the back-lit LCD screen, illuminated LEDs, remote PC and via SMS text alerts (with external modem).

In accordance with our commitment to continuous product improvement, we reserve the right to modify specifications without prior notice.

EME Power | +44 1829 863497 | emepowersolutions.com | sales@emeps.net

Dimensions	Length [mm]	Width [mm]	Hight [mm]	Weight [kg]	Fuel Capacity [LT]	Sound Level [dBA]
P250 Open	2980	1200	1692	1975	580	N/A
P250-S Canopied	3367	1260	2062	2658	580	72.3 dBA @ 7m
P275 Open	2980	1200	1692	2002	580	N/A
P275-S Canopied	3367	1260	2062	2685	580	72.4 dBA @ 7m
P340 Open	3230	1450	1801	2915	820	N/A
P340-S Canopied	4061	1510	2127	3310	820	72.5 dBA @ 7m

Engine
EME Power provides industrial diesel engines that meet ISO 8528 and ISO 3046 specifications. These engines are designed for heavy-duty applications, offering low fuel consumption and precise speed adjustment and regulation. They are equipped with mechanical or electronic governors mounted on the fuel pump and are available with oil, air, or water cooling systems to suit specific operational requirements.The engines are built with robust oil, fuel, and air filtration systems tailored for demanding operational conditions, ensuring long life and high performance. They are 4-stroke, direct-injection engines with all necessary limit and level sensors for safe operation. Engines designed exclusively for standby use are excluded from the production portfolio.

Alternator
EME Power incorporates original European-brand alternators in its generator sets, fully complying with international standards such as IEC 60034-1, ISO 8528-3, EN 55011, BS 4999-5000, and VDE 0530. These alternators deliver high efficiency and superior performance under all conditions and are certified to meet global quality standards.

Cooling Systems
Radiators in EME Power are selected from original options or approved vendor lists of engine manufacturers. These radiators are designed to optimise usability, spare part availability, high performance, and maximum efficiency. Remote-type radiators capable of handling temperatures up to 55°C can also be provided.

Frame
EME Power manufactures frames for all generator sets based on international standards. The frames are designed and constructed using plate panels or profiles to ensure high resistance to vibration and stresses, providing long-lasting durability.

Documentation
EME Power provides comprehensive documentation with every generator set, including:

- Maintenance and operation manual
- Engine and alternator manuals
- Controller usage and maintenance booklet
- Warranty certificate
- Electrical diagrams

Warranty
The warranty period for EME Power begins on the invoice date and covers up to 1 year or 1,000 operational hours, whichever comes first.

Authorised Dealer:

EME Power supplies generator sets for project requirements. Final configuration and commercial terms are confirmed in the written quotation.

In accordance with our commitment to continuous product improvement, we reserve the right to modify specifications without prior notice.

EME Power | +44 1829 863497 | emepowersolutions.com | sales@emeps.net