emepowersolutions.com
+44 1829 863497

PRODUCT DATASHEET

# MODEL P356-BWP

| 403 kVA | 322 kW | 356 kVA | 285 kW |
|---|---|---|---|
| ESP | ESP | PRP | PRP |

## 50 HZ | PRIME & STANDBY POWER




Illustration; final configuration may vary.

## DIESEL ENGINE

| | |
|---|---|
| ENGINE BRAND | Perkins |
| ENGINE MODEL | 2206A-E13TAG2 |
| ASPIRATION | Turbocharged |
| GOVERNOR | Electronic |

## ALTERNATOR

| | |
|---|---|
| BRAND | Stamford |
| MODEL | S4L1D-E41 |
| EXCITATION | Self Excited |
| INSULATION CLASS | H |
| VOLTAGE REGULATION | 1% |
| SPACE HEATER | Optional |

## GENERATOR SET - KEY PARAMETERS

| | |
|---|---|
| GENSET MODEL | P356-BWP |
| POWER PRP | 356 kVA / 285 kW |
| POWER ESP | 403 kVA / 322 kW |
| FREQUENCY / SPEED | 50 Hz / 1500 RPM |
| OUTPUT VOLTAGE | 400 / 230 V |
| WIRING METHOD | 3-phase, 4-wire |
| POWER FACTOR | 0.8 pf lagging |
| ENCLOSURE / NOISE | Canopied; 76 dB(A) @ 7 m |

## AUXILIARY SYSTEMS

| | |
|---|---|
| CONTROL MODULE | Deep Sea DSE 7320 MKII |
| COOLING RADIATOR | Tropical, 50 C ambient |
| FULL-LOAD CURRENT | 581.7 A at ESP |
| CIRCUIT BREAKER | Optional; sized to generator rating |
| COOLANT HEATER | Optional |
| STARTING BATTERY | Wet battery, maintenance-free |
| FUEL TANK | 500 litres |
| BASE FRAME | Base tank + AVM + battery holder |



Acoustic Vents



Premium DSE Controller



Easy Maintenance

## STANDARD SUPPLY

| | |
|---|---|
| INSTALLATION ACCESSORIES | AVMs, exhaust connection, silencer, standard connection parts and tool kit. |

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

emepowersolutions.com
+44 1829 863497

PRODUCT DATASHEET

# MODEL P356-BWP

| 403 kVA | 322 kW | 356 kVA | 285 kW |
|---|---|---|---|
| ESP | ESP | PRP | PRP |

## 50 HZ | PRIME & STANDBY POWER

## ENGINE TECHNICAL PARAMETERS - PERKINS 2206A-E13TAG2 - DIESEL

| | | | |
|---|---|---|---|
| STRUCTURAL FORM | 4 Stroke | COMBUSTION SYSTEM | Direct Injection |
| NUMBER OF CYLINDERS | 6 (In Line) | OIL CAPACITY | 40.0L |
| DISPLACEMENT | 12.5L | COOLANT CAPACITY | 51.4L |
| BORE / STROKE | 130mm / 157mm | MAX EXHAUST TEMP. | 630 ºC |
| COMPRESSION RATIO | 16.3:1 | EU EMISSIONS | None |
| ASPIRATION | Turbocharged | | |
| GOVERNOR | Electronic | | |
| COOLING METHOD | Liquid Cooled | | |
| SPEED | 1500 RPM | | |

## FUEL CONSUMPTION

| 50% Load | 75% Load | 100% Load | 110% Load |
|---|---|---|---|
| 37.00 litres/hour | 54.00 litres/hour | 71.00 litres/hour | 80.00 litres/hour |

## ALTERNATOR TECHNICAL PARAMETERS - STAMFORD S4L1D-E41

| | |
|---|---|
| RATED POWER AT 400 V | ESP 415.0 kVA / PRP 360.0 kVA |
| NUMBER OF POLES / LEADS | 4 / 12 |
| WINDING NUMBER | 311 |
| BEARING TYPE | 1 bearing |
| PROTECTION CLASS | IP23 |
| INSULATION CLASS | H |
| EXCITATION METHOD | Self Excited |
| VOLTAGE REGULATION | AS440 AVR / 1% |
| HARMONIC CONTENT | <5.00% |
| SHORT-CIRCUIT CAPACITY | >300% |
| SPACE HEATER | Optional |

## CONTROL SYSTEM - DSE 7320 MKII

| | |
|---|---|
| BRAND | Deep Sea Electronics |
| MODEL | DSE 7320 MKII |
| CONFIGURABLE INPUTS / OUTPUTS | 6 digital + 3 analogue senders / 6 outputs |
| KEY FEATURES | Auto-start, AMF control, LED indicators and event logging |

emepowersolutions.com
+44 1829 863497

PRODUCT DATASHEET

# MODEL P356-BWP

| 403 kVA | 322 kW | 356 kVA | 285 kW |
|---|---|---|---|
| ESP | ESP | PRP | PRP |

**50 HZ | PRIME & STANDBY POWER**




Illustration; final configuration may vary.

## DIMENSIONS & WEIGHT

| LENGTH (mm) | WIDTH (mm) | HEIGHT (mm) | WEIGHT (kg) |
|---|---|---|---|
| 4108 | 1508 | 2384 | 3978.1 |

Configuration: UK/EU Canopied / frame 2900EX / tank 500 L

## RATING CONDITIONS

| | |
|---|---|
| **RATING BASIS** | NTP conditions; confirm project derating requirements |
| **FREQUENCY / SPEED** | 50 Hz / 1500 RPM |
| **VOLTAGE / CONNECTION** | 400/230 V / series star |
| **POWER FACTOR** | 0.8 lagging |
| **COOLING PACKAGE** | Tropical radiator rated for 50 C ambient |
| **STANDARDS** | ISO 8528; IEC 60034 |

## DISCLAIMER

Ratings and component data are transcribed from the corresponding Welland Power configuration for 400 V, three-phase, 50 Hz operation and checked against the listed Perkins engine and Stamford alternator models. Dimensions, weight, tank and noise data apply only to the configuration stated above. Images are illustrative and are intentionally common across this range. Final build specification, GA drawing, breaker selection and site derating must be confirmed at order. Manufacturer specifications may change without notice.

Dealer contact details:

**EME POWER**

sales@emeps.net

+44 1829 863497 | emepowersolutions.com